

PRODUCT INFORMATION

HYDRAULIC ROLLER



These hydraulic rollers come standard with a maximum oil pressure of 250 bar. The necessary connections for this attachment require 1x double-acting hydraulic function, 1x single-side hydraulic hold and 1x leakage oil.

VERSATILE ATTACHMENT

TOBROCO-GIANT's hydraulic roller is a powerful and versatile tool designed to make your operations more efficient and effective. This roller is ideal for compacting different types of surfaces, from sand and gravel to asphalt and concrete.

| Width mm | Oil flow L/min | Impact force Kn | Weight kg | Skid | G1200 | G1500 | G2200E | G2300 | G2500 | G2700 | G2700E | G3500 | G5000 | GT5048 | Article nr. |
|-------------|-------------------|--------------------|--------------|------|-------|-------|--------|-------|-------|-------|--------|-------|-------|--------|-------------|
| 1.400 | 40-45 | 15 | 610 | x | x | + | ✓ | ✓ | ✓ | ✓ | ✓ | + | x | x | On request |
| 1.600 | 40-45 | 15 | 650 | x | x | x | + | + | ✓ | ✓ | ✓ | ✓ | + | ✓ | 6701051 |
| 1.800 | 40-45 | 15 | 690 | x | x | x | x | x | + | ✓ | ✓ | ✓ | ✓ | ✓ | On request |
| 2.000 | 40-45 | 15 | 730 | x | x | x | x | x | x | + | + | ✓ | ✓ | x | On request |

*Other width sizes on request.