

PRODUCT INFORMATION

FLAIL MOWER



These flail mowers come standard with Y-flails of 4 mm thickness and a maximum oil pressure of 270 bar. The required connections for this attachment demands 1x double-acting hydraulic function, 1x single-side hydraulic hold, 1x free hydraulic return and 1x leak oil connection.

WIDELY APPLICABLE ATTACHMENT

The extensive range of TOBROCO-GIANT mowers can be used widely for mowing roadsides, a lawn, meadow or park.

Version	Width mm	Oil flow L/min	Y-Flails STD pieces	Hammer flails pieces	Weight kg	Skid	G1200	G1500	G2200E	G2300	G2500	G2700	G2700E	G3500	G5000	GT5048	Article nr.
GA300	1.000	30	64	32	200	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	61343435P
GA300	1.200	36 - 42	80	40	250	✗	+	✓	✓	✓	✓	✗	✗	✗	✗	✗	61343460P
GA300	1.200	42 - 52	80	40	250	✗	✗	✗	✗	✗	✗	✓	✓	✗	✗	+	6134346P
GA300	1.400	36 - 42	88	44	260	✗	✗	+	✓	✓	✓	✗	✗	✗	✗	+	61343570P
GA300	1.400	45 - 52	88	44	260	✗	✗	✗	✗	✗	✗	✓	✓	+	✗	+	6134357P
GA400	1.400 HD	36 - 42	88	44	300	✗	✗	✗	✗	+	✓	✓	✓	✗	✗	+	61343590P
GA400	1.400 HD	51 - 62	88	44	300	✗	✗	✗	✗	✗	✗	✓	✗	✓	✓	+	6134359P
GA300	1.600	51 - 62	100	50	270	✗	✗	✗	✗	✗	✗	✓	✗	✓	✓	+	6134367P
GA400	1.600 HD	51 - 62	96	48	320	✗	✗	✗	✗	✗	✗	✓	✗	✓	✓	+	6134369P

Options	Article number
Double hitch	
Hydraulic side arm (additional DA hydr. function required)	
Y-Flails STD	61334601
Y-Flails HD	61334612
Hammer flails set steel, 3 mm	For a fine and even cut 6134606
Molded hammer flails STD	High grass and small branches 61344604
Molded hammer flails HD	High grass and small branches 61344604HD

