PRODUCT INFORMATION MODEL G2200E

Product information

i ioaaot iiiioiiii	1411011	
Battery	LFP battery (Lithium iron phosphate) 13,3 kWh / 260 Ah / 48V (195 kg)	
Driving mechanism	Electric four wheel drive with cardan shaft and 12.500 N pulling force 35 ltr/min (170 bar)	
Working hydraulics		
Tyres	10.0/75x15.3 AS Total machine width: 108 cm	
Driving speed	3-speed (0-4,5 km/h, 0-12 km/h, 0-18 km/h) Measured on standard tyres	
Standard version	ROPS / FOPS safetyroof • Incl. safety doors (L+R) Mechanically suspended seat • Incl. safety belt, armrest and extended backrest 1x Double acting hydraulic function on lifting arm, mechanical Working light (LED) front, on lifting arm Shunt coupling	
Hitch	GIANT Standard hydraulic quick change system	
Parking brake	Drum brakes	
Colour	GIANT yellow / GIANT grey / black	

Tyres

27x10.50-15 SKID (116 cm)
29x12.50-15 GRASS (123 cm)
31x15.50-15 AS (128 cm)
31x15.50-15 X-TRAC (128 cm)
31x15.50-15 SKID (128 cm)
31x15.50-15 GRASS (135 cm)
Twin wheels: 10,0/75x15,3 AS (2 pcs); Only possible in combination with 10,0/75x15,3 AS

Hydraulic connections front

Up to 2 additional double-acting hydraulic functions, proportional or mechanical operated Case drain

Free hydraulic return

Towbars and counterweights

Shunt coupling + Tow ball	
Counterweight (40 kg) under chassis (Max. 2)	

Electrical / Lighting

Various 12-volt connections	
Various work lights available in LED	
Flashing/warning light LED	
Flashers LED	



Technical data

Service weight ¹	2.200 kg
Lifting capacity	1.650 kg
Tipping load ²	1.645 kg
Lifting height 2,3	2.825 mm
Length without bucket	2.975 mm
Width ³	1.080 mm
Clearance height 3,4	2.300 mm

- ¹ Measured with standard version and earthbucket
- Measured on hinge point in straight position
 Measured on standard tyres

Tipping loads

Tipping loads are measured on a machine with a 390 Ah / 520





S	1.500 kg
Т	1.390 kg
U	1.080 kg
V	845 kg
W	2.360 kg
X	1.645 kg
Y	1.175 kg

Safetyroof

- · · · · · · · · · · · · · · · · · · ·	
ROPS / FOPS foldable safety roof	
ROPS / FOPS cabin	

