PRODUCT INFORMATION MODEL GS950TE



Battery	LFP battery (Lithium iron phosphate) 11,6 kWh / 228 Ah / 48V (96 kg)	
Driving mechanism	Electric motor nominal 16.7 kW (22 hp) • Permanent magnet motor Hydrostatic drive through 2 heavy wheel engines and 4.500 N pulling force Forwards, backwards and turning is easily done by spring loaded levers	
Driving hydraulics	180 bar	
Working hydraulics	38 ltr/min (180 bar)	
Tyres	Tracks 180 (Total width 90 cm)	
Driving speed	0-7,5 km/h • Measured on standard tyres	
Standard version	1x Double acting hydraulic function on lifting arm, mechanical Hip bracket adjustable Single-side hydraulic hold on additional function • On standard double acting hydraulic function on lifting arm Parallel guidance on lifting arm (by compensating cylinder) Height-adjustable driver's plateau Hand throttle Oil cooler Lifting eyes	
Hitch	GIANT Compact mechanical quick change system	
Color	GIANT yellow / GIANT grey / black	



Tracks 230 (100 cm)

Other options

1x extra double acting hydraulic function, mechanical

Tandem pump, front

- Includes 1x extra single-acting hydraulic function
- Only possible in combination with free return
- Max. 37,5 ltr/min at 150 bar
- Electrically switchable

Case drain at front				
Free hydraulic return				
Softbrake				
Various work lights available in LED or halogen				
12-volt connections				
Counterweight 60 kg				



Technical data

Service weight 1	1.125 kg
Lifting capacity	620 kg
Tipping load ²	1.020 kg
Lifting height ³	2.100 mm
Length without bucket	1.371 mm
Width ³	900 mm

- 1 Measured with earthbucket
- ² Measured on hinge point in straight position with counter-weight and driver ± 65 kg ³ Measured on standard tyres

Tipping loads





		Measured with 1x LFP battery	Measured with 2x LFP battery
	S	795 kg	880 kg
	Т	505 kg	560 kg
	U	345 kg	380 kg
	V	1.805 kg	2.000 kg
	W	805 kg	890 kg
	Χ	470 kg	520 kg
	Υ	270 kg	320 kg

